

MATERIAL NUMBER	# OF COLUMNS	# OF DIFF PAIR	DIM "A" MAX	DIM "B"	PTH ϕ
76460-*010	10	20	26.60	17.10	0.46
76460-*016	16	32	38.00	28.50	± 0.05
76460*020	10	20	26.60	17.10	0.39
76460-*026	16	32	38.00	28.50	± 0.05

76460-*0**

MODULE & TAIL PLATING TYPE
5 = RIGHT GUIDED LEAD-FREE

OF COLUMNS
10 = 10 COL 0.46 PTH
16 = 16 COL 0.46 PTH
20 = 10 COL 0.39 PTH
26 = 16 COL 0.39 PTH

SEE SHEET 1 EC NO: UCP2017-0743 DRWN: GONZALEZ01 2016/10/03 CHKD: APPR: TELO 2016/10/03	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
	$\nabla = 0$	mm	INCH	MM ONLY	4:1	METRIC		
	$\nabla = 0$	4 PLACES \pm ---	\pm ---	DRAWN BY	DATE	TITLE		IMPACT 100 OHM DC 2 PAIR SIGNAL MODULE GUIDE RIGHT SALES DWG
	$\nabla = 0$	3 PLACES \pm ---	\pm ---	JLAURX	2008/04/11			
		2 PLACES ± 0.13	\pm ---	CHECKED BY	DATE	molex		SD-76460-004
	1 PLACE ± 0.25	\pm ---	JLAURX	2008/04/11				
	0 PLACE \pm ---	\pm ---	APPROVED BY	DATE	MATERIAL NO.	DOCUMENT NO.	SHEET NO.	
			JLAURX	2008/04/11	SEE CHART	SD-76460-004	2 OF 2	
			ANGULAR $\pm 1/2^\circ$		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS					