





FM-5: TO PULL THROUGH A 3.5±1[.138±.039] HOLE, WITH MAXIMUM 0.8 [.031] PANEL AND 20±0.5 [.787] FAN THICKNESS.

FM-6: TO PULL THROUGH A 4.3±0.2 [.161±.008] HOLE, WITH MAXIMUM 3 [.118] PANEL AND 15 [.591] FAN THICKNESS.

FM-7: TO PULL THROUGH A 3.5±1 [.138±.039] HOLE, WITH MAXIMUM 0.8 [.031] PANEL AND 25-28 [.98-1.10] FAN THICKNESS.

STYLE 3

NOTES:

1. ALTERNATE UNITS FOR REFERENCE ONLY

В	SEE CO 200074	SK	11/30/07
Α	RELEASED FOR PRODUCTION, SEE ECN #1206	SK	08/11/06
REV.	DESCRIPTION	ENGR.	DATE

_								
	FAN MOUNT						DWG IN mm [IN]	R
CREATED USING SOLIDWORKS		FILE #: FM-X		DWN: SK	APP: SK	FINAL		
ĺ	TOLERANCES UNLESS NOTED	SHEET: 1 OF 1	SHEET SIZE: B	DT: 08/11/06	CHKD: SJ	PART#		PRINT
)/07 /06 TE	0~10=±0.1 10.01~30=±0.3 30.01~50=±0.5 ANG.=±1°	RE: RICHCO, INC.		RICHCO, INC. ENG@RICHCO-INC.COM (773) 539-4060		SEE TABLE		CA