

**Technical specification:**

Rated voltage: IEC 61076-2-101	4pos 160 V
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperatur range: IEC 60664-1	-30°C ... +70°C
Mating cycles: IEC 60512-9a	>=100


**Materials:**

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	PBT GF, UL 94
Coupling screw:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

**Installation specification:**

Recommended torque:	0,6 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 13: 36-000220


**Contact assignment:**



Part no:	Description:
43-12483	SAL - 12B - RSA4.1

DO NOT ALTER CAD DRAWING BY HAND  
Directive 2002/95/EC RoHS compliant

Index: a 09.03.11 VF Ä3767  
Coupling screw modified, spanner flats added, data sheet modified



dim. in mm

	date	name
drawn	20.10.08	Mankopf
appd.	20.10.08	Fromm

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.  
OWNERSHIP AND COPYRIGHT OF CONEC GmbH



title:  
**Male connector M12x1 axial,  
Profibus DP, terminal resistor**

dwg no:  
**43K1A787**

part no: **see table**