SPECIFICATION CONTROL DRAWING

CHEMINAX

.080

.104

75 OHM, AWG 28, 7 STRANDS OF AWG 36, COAXIAL CABLE

Date 7-31-09
Revision D

7528A1814


THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.

CONSTRUCTION DETAILS

ELECTRICAL CHARACTERISTICS

DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE DESIGNATED.

CHARACTERISTIC IMPEDANCE 75 ± 3 ohms, Method B CAPACITANCE 17.4 pF/ft. (nominal) VELOCITY OF PROPAGATION 78% (nominal)



SHIELD

JACKET

7erohal

AWG 38.

Tin-Coated Copper

ADDITIONAL REQUIREMENTS

ELECTRICAL

CONDUCTOR RESISTANCE
INSULATION RESISTANCE

74.0 ohms/1000 ft. (nominal) 10,000 megohms (minimum)

for 1000 ft.

JACKET FLAWS

SPARK TEST IMPULSE TEST 1.0 kV (rms) 6.0 kV (peak)

VOLTAGE WITHSTAND (DIELECTRIC) 1000 volts (rms) (minimum)

ENVIRONMENTAL

FLAMMABILITY HEAT SHOCK

225°C -30°C/3.00 inch mandrel

Method C

LOW TEMPERATURE-COLD BEND
VOLTAGE WITHSTAND
(Post Environmental)

1000 volts (rms), 1 minute

PHYSICAL

INSULATION (DIELECTRIC)

ELONGATION TENSILE STRENGTH 50% (minimum) 800 lbf/in² (minimum)

JACKET

ELONGATION TENSILE STRENGTH JACKET THICKNESS

SHIELD COVERAGE

150% (minimum) 1200 lbf/in² (minimum)

.012 inch (nominal) 90% (minimum)

Outer jacket color will be black (designated by a "-0" appended to the part number, e.g. 7528A1814-0) unless otherwise specified.

Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.

WEIGHT 7.2 lbs/1000 ft. (nominal)

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

The TE logo, Tyco Electronics, Cheminax, Raychem, Rayfoam and Zerohal are trademarks.

