

Part Number: 1523R






Product Description

CATV, Series 11, 14 AWG solid .064" bare copper-covered steel conductor, gas-injected foam polyethylene insulation, Duobond® II; aluminum braid shield (60% coverage), CMR PVC jacket.

Technical Specifications

Product Overview



Insulation

Material	Nominal Diameter
Gas-injected FPE - Foam Polyethylene	0.28 in

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Aluminum/Polyester/Aluminum	Bonded Duofoil®	100 %
Braid	2	AL - Aluminum		60 %

Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.4 in

Electrical Characteristics

Conductor DCR

Nomi	nal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
11 Or	nm/1000ft	4.1 Ohm/1000ft	4.1 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Shield 16.2 pF/ft Shielding: Multiple or Specialty

Inductance

Nominal Inductance
0.097 µH/ft

Impedance

Nominal Characteristic Impedance
75 Ohm

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.2 ns/ft	83 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)
5 MHz	0.38 dB/100ft
55 MHz	0.97 dB/100ft
211 MHz	1.81 dB/100ft
270 MHz	2.05 dB/100ft
300 MHz	2.15 dB/100ft
350 MHz	2.32 dB/100ft
400 MHz	2.47 dB/100ft
450 MHz	2.65 dB/100ft
550 MHz	2.94 dB/100ft
750 MHz	3.5 dB/100ft
870 MHz	3.84 dB/100ft
1000 MHz	4.23 dB/100ft

Voltage

Non-UL Voltage Rating	UL Voltage Rating
300 V RMS	300 V RMS

Temperature Range

Non-UL Temp Rating:	80°C
Operating Temp Range:	-30°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	54 lbs/1000ft
Max Recommended Pulling Tension:	260 lbs
Min Bend Radius/Minor Axis:	4 in

Standards

NEC/(UL) Specification:	CATVR, CMR
CEC/C(UL) Specification:	CMR
RG Type:	11/U Type
Series Type:	Series 11
RG / Series Type:	Series 11

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1666 Vertical Riser
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No

Part Number

Variants

Item #	Color
1523R 0101000	Black
1523R 010500	Black

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.